

100% OKOUME II/III

OUTDOOR PANELS



DESCRIPTION

100% Okoumé Plywood

USINGS

This product is especially suitable for outdoor using

ADVANTAGES

- ✓ Naturally sustainable wood
- ✓ Excellent mechanical resistance

COMPOSITION

Face 1 : Okoume rotary cut veneer 10/10° quality II

Face 2 : Okoume rotary cut veneer 10/10° quality III

Inner layers in selected peeled okoume veneers,

WOOD SPECY

Okoume (500 kg/m³ +/-10%)

GLUING

EN 314-2 : Class 3 (EN 636-3) Exterior using

SIZES

Regular sizes in mm : 2500x1220 - 3100x1530

Special sizes in mm : 2500x1530 - 3100x1220

THICKNESSES

mm	4	6	8	10	12	15	18	22	25	30
plies	3	5	5	7	7	9	11	13	13	15

Surface finishing sanded 2 faces

For any other thickness and size, please contact us

OPTIONS

Cut at size, CNC milling, grooving, varnishing

SAS ALLIN

RUE DE LA COUARDE - F-79270 LE VANNEAU

Tel : +33 5 49 35 00 02 – Fax : +33 5 49 35 02 64

E-mail : allin-sa@allin.fr – Site web : www.allin.fr